



MMX-22

Order No.: 0202770

Price upon request

PRODUCTINFOS

6-channel audio mixer,

- 2 mono input channels, each with gain control, 3-way equalizer and pan pot
- 2 stereo input channels, each with 3-way equalizer and balance control
- Adjustable aux send output
- Control room function
- Tape record/play connections
- +48 V phantom power, can be switched centrally
- Adjustable headphone output
- Stereo LED level display
- Power is provided via enclosed power supply

TECHNICAL SPECIFICATIONS

MMX-22

Input channels	6
Number of mix/mono	2

MMX-22

No. of stereo	2
Mic input	0.5 mV, bal., 2 x 3-pole XLR
Line input	10 mV, bal. (stereo), 2 x 6.3 mm jack L/R 1 mV (mono), 2 x 6.3 mm jack
Tape (play)	650 mV, 1 x RCA L/R
Aux input	100 mV, 1 x 6.3 mm jack L/R
Master output	650 mV, 1 x 6.3 mm jack L/R
Aux output	9.5 V, 1 x 6.3 mm jack
Control room	2 V, 1 x 6.3 mm jack L/R
Tape (rec)	100 mV, 1 x RCA L/R
Headphones	$\geq 8 \Omega$, 1 x 6.3 mm jack
Frequency range	20-20,000 Hz
THD	< 0.05%
S/N ratio	> 74 dB
Crosstalk	-63 dB
Equalizer bass	± 15 dB/80 Hz
Equalizer midrange	± 15 dB/2.5 kHz
Equalizer treble	± 15 dB/12 kHz
Phantom power	+48 V
Power supply	via encl. power supply
Admiss. ambient temp.	0-40 °C
Width	190 mm
Height	50 mm
Depth	260 mm
Weight	1.7 kg