



NWR-6400

Order No.: 0180176

Price upon request

PRODUCTINFOS

PROJECT Line 64-channel network video recorder

- Video compression for recordings: H.264, H.265
- Bandwidth: 640 Mbps, each channel: 10 Mbps max.
- 8 x SATA hard disk max. with 8 TB each
- Linux operating system for maximum operating reliability
- Automatic camera identification due to UPnP protocol
- P2P communication (peer-to-peer)
- Supports PTZ cameras
- Synchronised audio and video recording
- 4 different user access levels can be set up
- Mobile Client for iPhone, iPad, Android
- Smart Home Ready
- E-MAP for indicating camera positions
- Dual streaming for bandwidth management
- Log system for logging status of the system, camera and access
- Digital PTZ and multi-window display
- Intelligent search function, search for distant or foreign objects, general movements, loss of focus, concealed cameras
- Data export possible as image file (BMP, JPG), video file (ASF, AVI) or backup file (DAT)
- Automatic backup via FTP
- 16 x alarm input, 1 x alarm output
- 1 x audio input, 1 x audio output
- An optional PoE switch or PoE midspan (e.g. TPE-TG80G, POE-130MID) is required for supplying the

power to PoE network cameras

- OSD: German, English, French, Italian, Russian, Spanish and other languages
- Instruction manual: English

Supplied w/o hard disks. Matching SATA hard disks are available at option.

TECHNICAL SPECIFICATIONS

NWR-6400

Video recorder

-

Video inputs	64 IP-based video channels
Video outputs	HDMI™ (4K max.), VGA
Audio inputs	1
Audio outputs	1
Resolution	3840 x 2160 pixels max.
Video compression	H.264, H.265
Recording	dep. on the resolution of connected cameras
Menu adjustments	on-screen menu (OSD)
Recording mode	alarm, motion-triggered, continuous recording, digital input, manual, timer
Search mode	distant or foreign objects, general movements, loss of focus, concealed cameras
Lettering	per camera channel
Security	4 user access levels
Video loss detection	yes
Alarm inputs	16
Alarm outputs	1
Interfaces	1 x RJ45 (100/1,000 Mbps)
	1 x USB 3.0
	2 x USB 2.0
	1 x eSATA
Hard disks	optional, up to 8 x SATA II, 64 TB max.
Power supply	~ 230 V/50 Hz/300 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	300 VA
Admiss. ambient temp.	0-40 °C

NWR-6400

Dimensions	440 x 89 x 460 mm
Width	440 mm
Height	89 mm
Depth	460 mm
Weight	7 kg