



## PA-1200

Order No.: 0170710

**Price upon request**

### PRODUCTINFOS

#### 4-zone mono PA mixing amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- Chime, continuous sound and wailing sound, automatic mute, chime can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs
- 15 V phantom power for channels 2 and 3
- Insertions for various functions are available at option
- 482 mm (19") rack installation with mounting frame PA-1200RM, available at option
- Mains operation and 24 V emergency power operation

### TECHNICAL SPECIFICATIONS

#### PA-1200

Peak output power	170 W
Power rating	120 W
Channels	5
Zones	4

**PA-1200**

Inputs	1.5 mV/600 $\Omega$ (mic),
	150 mV/47 k $\Omega$ (line),
	1 mV/47 k $\Omega$ (phono)
Frequency range	80-15,000 Hz
Equalizer bass	$\pm 10$ dB/100 Hz
Equalizer treble	$\pm 10$ dB/10 kHz
S/N ratio	> 60 dB (mic),
	> 70 dB (line)
THD	< 1%
Mains voltage	$\sim 230$ V
Mains frequency	50 Hz
Power consumption, operation	280 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 11 A
Admiss. ambient temp.	0-40 $^{\circ}\text{C}$
Width	420 mm
Height	122 mm
Depth	350 mm
Weight	12.28 kg
Connections	1 x 6.3 mm jack (mic input),
	3 x XLR, bal. (mic/line inputs),
	1 x RCA L + R (line input),
	1 x RCA L + R (phono/line input),
	1 x twin spring-loaded terminal (telephone input),
	1 x twin spring-loaded terminal (tuner output),
	1 x twin spri