



PA-888D

Order No.: 17.6730

EUR 249,00

RRP*

PRODUCTINFOS

Mono class D PA mixing amplifier

- 1 x 60 W
- Class D concept with a high efficiency to cut energy costs
- Silent operation due to fanless cooling concept
- 2 microphone inputs, 1 aux input
- Chime, siren and fog horn (saved as MP3 files in internal memory, other files can be played via USB port), adjustable level

3

- Bass, treble and master controls
- 6-step LED level display
- Protective circuit with LED indication for protection
- Mains operation or 12-24 V battery operation

TECHNICAL SPECIFICATIONS

PA-888D

Channels



PA-888D

Power rating 60 W Power rating at 4 Ω 60 W Power rating at 8 Ω 35 W Power rating at 100 V 60 W Peak music power output (P_{MAX}) 80 W

Inputs $3.5 \text{ mV/1 k}\Omega \text{ (mic),} \\ 35 \text{ mV/2 k}\Omega \text{ (aux)}$

Frequency range 100-18,000 Hz Equalizer bass $\pm 10 \text{ dB/}100 \text{ Hz}$ Equalizer treble $\pm 5 \text{ dB/}10 \text{ kHz}$

S/N ratio > 67 dB THD < 0.05%

~ 230 V/50 Hz/220 VA, DC 12 V/8 A, DC 24 V/4 A

Operating voltage (possible alternative) DC 12 V, DC 24 V

Power supply (possible alternative) DC 3.9 A Admiss. ambient temp. $0-40 \, ^{\circ}\text{C}$

Dimensions 319 x 92 x 240 mm

Width 280 mm
Height 100 mm
Depth 280 mm
Weight 4.4 kg

2 x 6.3 mm jack (mic), 1 x 6.3 mm jack (aux),

Connections 1 x micro USB

1 x micro USB,

screw terminals (speakers)

^{*} Important Notice: The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.