



PA-900S

Order No.: 17.2080

EUR 389,00

RRP *

PRODUCTINFOS

Mono PA power amplifier

- 1 x 120 W
- Silent operation due to fanless cooling concept
- 2-way tone control
- Switchable low cut filter
- Speaker outputs via screw terminals
- Feed-through output (link)
- Mains operation or 24 V emergency power operation
- 482 mm (19") rack installation with supplied mounting brackets

TECHNICAL SPECIFICATIONS

PA-900S

Channels	-
Power rating	120 W
Peak music power output (P_{MAX})	160 W
Output impedance	4 Ω , 70 V/ 100 V
Inputs	765 mV (line)

PA-900S

Frequency range	50-15,000 Hz, ± 3 dB
Equalizer bass	± 10 dB/100 Hz
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 80 dB
THD	< 0.5%
Power supply	~ 230 V/50 Hz/300 VA, DC 24 V/9 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	300 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 9 A
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 88 x 275 mm, 2 RS
Width	482 mm
Height	88 mm
Depth	275 mm
Rack spaces, RS	2
Weight	9.5 kg
Connections	1 x XLR, screw terminals (line in), 1 x XLR (line out), screw terminals (speakers)

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.