



## PAB-112MK2

Order No.: 0252240

**Price upon request**

### PRODUCTINFOS

#### **The 100 series of high power capability with a nice sound**

provides PA speaker systems for PA and DJ applications and is suitable for medium-sized to large function rooms. The timeless plastic cabinets are also very robust and have extensively been tested in practical operation.

#### **DJ and power speaker system, 500 W, 8 Ω**

- High-performance full range system of high efficiency
- Robust plastic cabinet
- 30 cm (12") bass speaker with diecast aluminium basket
- 25 mm (1", 34 mm voice coil) horn tweeter
- Bass-reflex system
- Multi-purpose positioning and installation options
- M8 threaded inserts (2 x top, 1 x bottom)
- 2 x SPEAKER jack, in/out
- Stand sleeve and carrying handle
- Protective cover for speaker systems PAB-112BAG is available at option

### Beat 06/2012

“The PAB-112MK2 is a really good entry-level unit for getting hooked on DJing. It provides a powerful and well-balanced sound and is of a neat workmanship ... the unit is highly enjoyable. Features a very good price-performance ratio.”

- + neat workmanship
- + clear sound
- + lightweight

### tastenwelt 02/2012

“The plastic housings are of neat workmanship ... the MMX-842USB is a good choice ... the STA-225 features all standard protective circuits, even a clip limiter can be activated as required. A display shows useful information on the operation. The system tested provided a really appealing sound: a nice deep bass reproduction and a clear midrange of the 12" speakers and a full and clear reproduction of the high frequencies, too. With the support of a subwoofer, the volume which can be achieved is already sufficient to show a great performance at smaller to medium-sized events. Neither the active bass speaker nor the passive top parts provide an unpleasant or even overstrained sound.”

(PA setup of PAB-112MK2, PSUB-115AK, STA-225, MMX-842USB)

## TECHNICAL SPECIFICATIONS

### PAB-112MK2

Active/passive	passive
Transmission method	cable
Total power rating	500 W
Power rating (RMS)	250 W
Impedance	8 Ω
Frequency range	55-20,000 Hz
System	12/2 full range
Bass speaker	30 cm (12") bass speaker
Tweeter	25 mm (1", 34 mm voice coil) horn tweeter
Number of speakers	2
Speaker size	30 cm (12")
Sensitivity	98 dB/W/m
Max. rated SPL	122 dB
Housing material	plastic
Colour	black
Mounting device	M8 threaded inserts, stand sleeve
Admiss. ambient temp.	0-40 °C

**PAB-112MK2**

Dimensions	430 x 580 x 310 mm
Width	430 mm
Height	580 mm
Depth	310 mm
Weight	14.62 kg
Inputs	1 x SPEAKER
Outputs	1 x SPEAKER, par. out
Replacement voice coil	PAB-115/VC (version 06/2015 or higher), PAB-128/VC
Accessories	PAB-112BAG