



PAB-515/BL

Order No.: 0248250

Price upon request

PRODUCTINFOS

The Professional PA Speaker Systems of the 500 Series

in a trapezoid plastic cabinet have especially been developed to meet the requirements of professional applications. They are equipped with a coated, moisture-proof cone.

Professional PA speaker system, 600 W, 8 Ω

- Full range system of high power capability and of very high efficiency
- Robust plastic cabinet
- 38 cm (15") bass speaker with diecast aluminium basket and coated cone
- 25 mm (1", 44 mm voice coil) horn tweeter
- Bass-reflex system
- High-quality crossover network
- Multi-purpose positioning and installation options
- M8 threaded inserts at the top and bottom
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve and ergonomic carrying handle

TECHNICAL SPECIFICATIONS

PAB-515/BL

Active/passive	passive
Transmission method	cable
Total power rating	600 W
Power rating (RMS)	300 W
Impedance	8 Ω
Frequency range	45-18,500 Hz
System	2-way bass-reflex
Bass speaker	38 cm (15")
Tweeter	dyn. mid-high range horn speaker
Number of speakers	2
Speaker size	38 cm (15")
Sensitivity	102 dB/W/m
Max. rated SPL	126 dB
Housing material	plastic
Colour	black
Mounting device	M8 threaded inserts, stand sleeve
Admiss. ambient temp.	0-40 °C
Dimensions	450 x 670 x 345 mm
Width	450 mm
Height	670 mm
Depth	345 mm
Weight	23 kg
Inputs	1 x NEUTRIK SPEAKON
Outputs	1 x NEUTRIK SPEAKON par. out
Accessories	PAB-515BAG