



PAB-58/SW

Order No.: 0131910

Price upon request

PRODUCTINFOS

This particularly attractive and efficient series of PA speaker systems

is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality.

Pairs of high-quality PA speakers, 30 W, 8 Ω

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks with a perfect long-term stability, e.g. due to consistently applying film capacitors
- Really fast and brilliant sound of high efficiency and high dynamic range, particularly suitable for PA applications of modern music with higher volume levels
- Supplied with wall bracket

TECHNICAL SPECIFICATIONS

PAB-58/SW

Active/passive	passive
Total power rating	50 W
Power rating (RMS)	30 W
Impedance	8 Ω
Frequency range	75-22,000 Hz
System	2-way
Bass speaker	polypropylene bass speaker
Tweeter	dome tweeter
Number of speakers	2
Sensitivity	92 dB/W/m
Max. rated SPL	107 dB
Housing material	ABS plastic
Colour	black
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	160 x 250 x 150 mm
Width	160 mm
Height	250 mm
Depth	150 mm
Weight	2.2 kg
Inputs	speaker screw terminal