



## PAB-68/SW

Order No.: 0131930

**Price upon request**

### PRODUCTINFOS

#### **This particularly attractive and efficient series of PA speaker systems**

is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality.

#### **Pairs of high-quality PA speakers, 40 W, 8 Ω**

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance, bass-reflex
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks
- Very well-balanced and clear sound which also impresses with a genuine reproduction of vocals and demanding music
- LED at the front for indicating the level
- Supplied with wall bracket

## TECHNICAL SPECIFICATIONS

### PAB-68/SW

Active/passive	passive
Total power rating	70 W
Power rating (RMS)	40 W
Impedance	8 $\Omega$
Frequency range	55-22,000 Hz
System	2-way
Bass speaker	polypropylene bass speaker
Tweeter	dome tweeter
Number of speakers	2
Sensitivity	90 dB/W/m
Max. rated SPL	106 dB
Housing material	ABS plastic
Colour	black
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	210 x 350 x 200 mm
Width	210 mm
Height	350 mm
Depth	200 mm
Weight	3.9 kg
Inputs	speaker screw terminal