



PAB-6WP/WS

Order No.: 0253560

Price upon request

PRODUCTINFOS

Weatherproof PA speakers with IP classification.

Exactly the right speakers whenever a high sound quality, a high volume capability and a respective resistance to all weather conditions are required. Ideally suited for permanent open-air applications, e.g. at fairground attractions, PA applications in pedestrian areas, at sports facilities and wherever a weather-protected installation of the speakers is not possible.

Weatherproof high-performance PA speaker system, 100 W

- Compact 2-way bass-reflex system in an ABS cabinet
- 100 V or 8 Ω operation, selectable
- 16 cm bass speaker with coated carbon fibre cone
- 30 mm dome tweeter with horn front attachment
- Front grille with water-repellent gauze
- Recessed connection terminal with cover plate and high-strength cable gland
- Metal parts and wall bracket made of stainless steel
- Ball-proof according to DIN 18032, Part 3

PROSOUND 05/2011

“The cabinets give a solid impression ... and meet IP45 requirements. All four speaker systems are suitable for pleasant background music ... the large PAB-8WP/WS is capable of quite high volume levels ... however, the small ones should not be underestimated ... these speaker systems are impressive and the price is quite reasonable for weatherproof speaker systems.”

TECHNICAL SPECIFICATIONS

PAB-6WP/WS

Active/passive	passive
Transmission method	100 V
Total power rating	180 W
Power rating (RMS)	100/50/25 W
Impedance	8 Ω
Frequency range	42-19,000 Hz
System	2-way bass-reflex
Bass speaker	16 cm bass speaker
Tweeter	30 mm dome
Number of speakers	2
Speaker size	16 cm
Sensitivity	90 dB/W/m
Max. rated SPL	110 dB
Housing material	ABS plastic
Colour	white
Mounting device	mounting bracket
Protected against ball rebound	yes
Protection class	IP45
Admiss. ambient temp.	-10 °C to +40 °C
Dimensions	200 x 370 x 240 mm
Width	200 mm
Height	370 mm
Depth	240 mm
Weight	7.1 kg
Inputs	screw terminal