



PAB-88/SW

Order No.: 0131950

Price upon request

PRODUCTINFOS

This particularly attractive and efficient series of PA speaker systems

is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality.

Pairs of high-quality PA speakers, 75 W, 8 Ω

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance, bass-reflex
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks with a perfect long-term stability, e.g. due to consistently applying film capacitors
- Impress by a really fast and brilliant sound of high efficiency and a high dynamic range and are particularly optimised for PA applications of modern music of higher volume levels
- LED at the front for indicating the level
- Supplied with wall bracket

TECHNICAL SPECIFICATIONS

PAB-88/SW

Active/passive	passive
Total power rating	120 W
Power rating (RMS)	75 W
Impedance	8 Ω
Frequency range	40-20,000 Hz
System	2-way bass-reflex
Bass speaker	polypropylene bass speaker
Tweeter	dome tweeter
Number of speakers	2
Sensitivity	92 dB/W/m
Max. rated SPL	111 dB
Housing material	ABS plastic
Colour	black
Mounting device	2 x thread M6
Admiss. ambient temp.	0-40 °C
Dimensions	250 x 420 x 240 mm
Width	250 mm
Height	420 mm
Depth	240 mm
Weight	7 kg
Inputs	speaker screw terminal