



## PAK-108MK2

Order No.: 0252260

**Price upon request**

### PRODUCTINFOS

#### **The 100 series: high power capability, excellent sound**

This series offers PA speaker systems for PA and DJ applications which are suitable for medium-sized to large function rooms. The plastic cabinets of timeless design are very robust and have extensively been tested in practical operation.

The active PAK version features a warm sound due to well-approved transistor technology and ensures sufficient dynamic reserves and power reserves.

#### **Active DJ and power speaker system, 130 W**

- Full range system of high efficiency
- Robust plastic cabinet
- 20 cm (8") bass speaker with diecast aluminium basket
- 25 mm (1", 34 mm voice coil) horn tweeter
- Bass-reflex system
- High-performance active module
- Multi-purpose positioning and installation options
- M8 threaded inserts (2 x top, 1 x bottom)
- XLR and RCA L/R (line), XLR (mic)

- Stand adapter for standard stands
- Protective cover for speaker systems PAB-108BAG is available at option

### **djmagazin.de 05/2012**

“With quiet, so-called dinner music, both of the speaker systems provide a well-balanced sound with a very good reproduction of all frequencies. At higher volume levels, both of the speaker systems provide a reliable reproduction and a neutral sound. Suitable for versatile applications. Also provided a surprisingly powerful reproduction outdoors which is still well audible at a distance. Both speaker systems received a grade 1!”  
(PAK-108MK2 and PAK-110MK2 in the test)

## **TECHNICAL SPECIFICATIONS**

### **PAK-108MK2**

Active/passive	active
Transmission method	cable
Total output power	130 W
Power rating (RMS)	75 W
Frequency range	60-20,000 Hz
Input signal	125 mV (line, XLR, bal.), 100 mV (line, RCA), 6.5 mV (mic, bal.)
System	8/2 full range
Bass speaker	20 cm (8") bass speaker
Tweeter	25 mm (1", 34 mm voice coil) horn tweeter
Number of speakers	2
Speaker size	20 cm (8")
Sensitivity	94 dB/W/m
Max. rated SPL	112 dB
Housing material	plastic
Colour	black
Mounting device	M8 threaded inserts, stand sleeve
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/200 VA
Dimensions	290 x 405 x 220 mm
Width	290 mm
Height	405 mm
Depth	220 mm
Weight	9 kg

**PAK-108MK2**

Inputs	XLR and RCA L/R (line)
	XLR (mic)
Outputs	XLR, bal. (par. line out)
Replacement voice coil	PAB-128/VC
Other features	integr. limiter
Accessories	PAB-108BAG