



PAK-308M/SW

Order No.: 0255110

Price upon request

PRODUCTINFOS

Multi-purpose PA speakers for versatile applications:

the 300 series. They can be used for both fixed installations and mobile applications. Ideally suited for powerful PA applications of good level stability in rooms as well as for rearfill applications and sidefill applications. The very compact and easy-to-transport systems are also very well-suited for mobile applications when combined with suitable subwoofers, e.g. PSUB-12AKA or PSUB-15AKA and as small floor monitors.

Universal active PA speaker system with DSP, 500 W

- Compact 8/2 full range bass-reflex system
- 20 cm (8") coaxial speaker system with 25 mm (1", 44 mm voice coil) horn tweeter
- DSP-controlled 2-channel amplifier system, bass: class D, tweeter: analogue
- Max. sound pressure at nominal power: 118 dB, music: 121 dB, peak: 124 dB
- 3 selectable presets: music, flat and low cut (120 Hz)
- Indication for signal and clip
- Feed-through outputs and mix output
- High-quality cabinet made of multiplex wood with protective metal grille
- Multi-purpose positioning and installation options, especially as a floor monitor

- M10 threaded inserts for bracket mounting, M8 threaded insert as a mounting safeguard
- Supplied with mounting bracket and integrated stand sleeve

www.musicnstuff.de 07/2014

“The PAK-308M/SW is capable of really high volume levels. We clearly recommend to use the PAK-308M/SW from IMG Stage Line as follows: In the rehearsal room, it is ideally suited as a PA system or optionally as a monitor speaker. For on-the-road applications, you can simply take it with you, set it up on stage and enjoy the sound in the usual manner. This speaker is a great choice because most of the wedge speakers vegetating in clubs or bars are usually inadequate. Oh, by the way: the new monitor speakers PAB-308M/SW are also available as passive versions.”

SOUNDCHECK 08/2014

“Impresses by a powerful sound performance of high level stability and thus, is suitable for fixed installations as well as vertaile mobile applications. During the practical test, the floor monitor also impressed with a respectable and distortion-free sound at higher volume levels.”

TECHNICAL SPECIFICATIONS

PAK-308M/SW

Active/passive	active
Transmission method	cable
Total output power	500 W
	DSP-controlled, 370 W (300+70)
Power rating (RMS)	bass: 300 W
	tweeter: 70 W
Frequency range	60-20,000 Hz
Input signal	775 mV/20 kΩ (line, bal.), 10 mV/20 kΩ (mic, bal.)
System	8/2 full range bass-reflex
Bass speaker	20 cm (8") coaxial speaker
Tweeter	25 mm (1", 44 mm voice coil) horn tweeter
Number of speakers	2
Speaker size	20 cm (8")
Sensitivity	97 dB/W/m
Max. rated SPL	118 dB
Housing material	multiplex
Colour	black

PAK-308M/SW

Mounting device	M10 threaded inserts (bracket mounting), M8 threaded insert (mounting safeguard), stand sleeve
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/350 VA
Dimensions	340 x 303 x 379 mm
Width	340 mm
Height	303 mm
Depth	379 mm
Weight	10.75 kg
Inputs	2 x comb. XLR/6.3 mm (line/mic A, line B)
Outputs	2 x XLR, par. out, 1 x XLR MIX out
Other features	DSP-controlled limiter