



20W

RBT-56

Order No.: 0013210

Price upon request

PRODUCTINFOS

Hi-fi ribbon tweeter, 10 W, 4 Ω

- Magnetostatic tweeter of compact size
- Neodymium magnet system
- Fine and brilliant reproduction of the high frequencies
- Round cone with Kapton and aluminium film
- For use from 5,000 Hz on
- Plastic sound diffuser panel (front)

TECHNICAL SPECIFICATIONS

RBT-56

| | |
|---|-----------------|
| Impedance (Z) | 4 Ω |
| Frequency range | 5,000-40,000 Hz |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | 5,000 Hz |
| Power rating (RMS) | 10 W |

RBT-56

| | |
|-------------------------------|-----------------------|
| Peak music power output (MAX) | 20 W |
| Sensitivity | 90 dB/W/m |
| DC resistance (Re) | 3.5 Ω |
| Magnet diameter | magnetostatic speaker |
| Mounting cutout | \varnothing 40 mm |
| Mounting depth | 10 mm |
| Mounting hole diameter | \varnothing 48 mm |
| Dimensions | 56.5 mm |
| Outside diameter | \varnothing 56.5 mm |
| Width | \varnothing 56.5 mm |
| Depth | 10 mm |
| Admiss. ambient temp. | 0-40 °C |
| Weight | 0.035 kg |
| Packing unit | 1 |