



RL-1ENABDS

Order No.: 0163690

Price upon request

PRODUCTINFOS

PA A/B sound projector for wall mounting,

with EN 54-24 certification for voice evacuation systems with A/B speaker distribution according to EN 60849.

- 100 V line technique
- 13 cm full range speaker with dual voice coil
- 2 x 100 V transformator with power taps on the cable 6/3/1.5 W
- Connection via 2 x 4-core cable (length: 1.5 m)
- Metal housing with front protective grille
- Supplied with pan/tilt bracket and mounting accessories

TECHNICAL SPECIFICATIONS

RL-1ENABDS

Active/passive passive

Transmission method	100 V
---------------------	-------

RL-1ENABDS

Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	80-20,000 Hz
Full range speaker	13 cm, dual voice coil
Speaker size	13 cm
Sensitivity	93 dB/W/m
Max. rated SPL	101 dB
Radiation angle, horizontal	130°
Radiation angle, vertical	130°
Housing material	aluminium
Colour	white
Mounting device	bracket
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 144 mm x 210 mm
Width	Ø 144 mm
Depth	210 mm
Weight	2.3 kg