



SA-100

Order No.: 0254120

Price upon request

PRODUCTINFOS

Compact universal stereo amplifier, 50 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- USB port on the front panel for power supply and for charging external devices
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

TECHNICAL SPECIFICATIONS

SA-100

Peak output power	2 x 50 W
Power rating	50 W
Power rating at 4 Ω	2 x 25 W
Power rating at 8 Ω	2 x 20 W
Channels	2

SA-100

Inputs	140 mV/46 k Ω (PC, CD, aux)
	140 mV/12 k Ω , 25 mV/32 k Ω (player)
Frequency range	20-20,000 Hz
Equalizer bass	± 12 dB
Equalizer treble	± 12 dB
S/N ratio	> 70 dB
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	150 VA
Admiss. ambient temp.	0-40 °C
Width	212 mm
Height	56 mm
Depth	250 mm
Weight	2.6 kg
Connections	1 x RCA L/R (PC),
	1 x RCA L/R (CD),
	1 x RCA L/R (aux),
	1 x 3.5 mm jack (player), 4 x spring-load. speaker term. (speakers)