



SA-230/SW

Order No.: 0250740

Price upon request

PRODUCTINFOS

Universal stereo mixing amplifier, 50 W

Sing along! The clearly arranged user surface of the SA-230/SW makes listening to music and especially making music really enjoyable. One of the three stereo line sources at a time and three mono microphone sources can be mixed together without any problems. When combined with special karaoke CDs or DVDs, features like "one-touch karaoke" or "vocal partner" are available. An adjustable digital echo can be added to the microphone channels as an effect. The fanless cooling concept of the amplifier ensures a silent operation. The latest protective circuits provide protection against overload, overheating and short circuit.

- Silent operation due to fanless cooling concept
- 3 stereo line inputs
- 3 mono microphone inputs on the front panel, each with gain control
- Adjustable digital echo for the microphone inputs
- Karaoke feature
- Vocal partner feature
- LEDs for indicating level control and active line inputs
- Controls for volume, bass, treble, balance and digital echo
- Stereo record output
- 482 mm (19") rack installation, 1 RS, with supplied mounting brackets

TECHNICAL SPECIFICATIONS

SA-230/SW

Peak output power	2 x 50 W
Power rating	50 W

SA-230/SW

Power rating at 4 Ω	2 x 25 W
Power rating at 8 Ω	2 x 20 W
Channels	2
Inputs	175 mV/8 k Ω (line) 2.5 mV/3.5 k Ω (mic)
Frequency range	20-20,000 Hz
Equalizer bass	\pm 10 dB
Equalizer treble	\pm 10 dB
S/N ratio	62 dB
Mains voltage	\sim 230 V
Mains frequency	50 Hz
Power consumption, operation	150 VA
Admiss. ambient temp.	0-40 $^{\circ}$ C
Width	432 mm
Height	45 mm
Depth	275 mm
Rack spaces, RS	1
Weight	3.8 kg
Connections	1 x RCA L/R (line), 1 x 6.3 mm jack (mic), 1 x RCA L/R (rec.), 4 x spring-load. speaker term. (speakers)