



SA-50

Order No.: 0254620

Price upon request

PRODUCTINFOS

Compact universal stereo amplifier, 25 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

TECHNICAL SPECIFICATIONS

SA-50

| | |
|----------------------------|------------|
| Peak output power | 2 x 25 W |
| Power rating | 25 W |
| Power rating at 4 Ω | 2 x 12.5 W |
| Power rating at 8 Ω | 2 x 10 W |
| Channels | 2 |

SA-50

| | |
|------------------------------|---|
| Inputs | 115 mV/12 k Ω (PC), |
| | 115 mV/12 k Ω (CD), |
| | 115 mV/12 k Ω (aux), |
| | 115 mV/12 k Ω (player, high), |
| | 20 mV/32 k Ω (player, low) |
| Frequency range | 20-20,000 Hz |
| Equalizer bass | ± 12 dB |
| Equalizer treble | ± 12 dB |
| S/N ratio | > 65 dB |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 50 VA |
| Admiss. ambient temp. | 0-40 °C |
| Width | 212 mm |
| Height | 56 mm |
| Depth | 200 mm |
| Weight | 1.8 kg |
| Connections | 1 x RCA L/R (PC), |
| | 1 x RCA L/R (CD), |
| | 1 x RCA L/R (aux), |
| | 1 x 3.5 mm jack (player), |
| | 4 x spring-load. speaker term. (speakers) |