



SP-8/150PA

Order No.: 0101680

Price upon request

PRODUCTINFOS

PA bass-midrange speaker, 150 W, 8 Ω

- Good medium efficiency
- Wide bandwidth radiation for midrange applications

TECHNICAL SPECIFICATIONS

SP-8/150PA

Impedance (Z)	8 Ω
Frequency range	f3-8,000 Hz
Resonant frequency (fs)	88 Hz
Power rating (RMS)	150 W
Peak music power output (MAX)	300 W
Sensitivity	96 dB/W/m
Suspension compl. (Cms)	0.16 mm/N

SP-8/150PA

Moving mass (Mms)	20 g
Mech. Q factor (Qms)	4.12
Electr. Q factor (Qes)	0.48
Total Q factor (Qts)	0.43
Equivalent volume (Vas)	12 l
DC resistance (Re)	6.9 Ω
Force factor (BxL)	12.60 Tm
Voice coil induct. (Le)	0.6 mH
Voice coil diameter	\varnothing 50 mm
Voice coil former	Kapton
Linear excursion (X_{MAX})	\pm 1.25 mm
Eff. cone area (Sd)	219 cm ²
Magnet weight	1.1 kg
Magnet diameter	\varnothing 140 mm
Mounting cutout	\varnothing 185 mm
Mounting depth	90 mm
Dimensions	\varnothing 210 mm x 98 mm
Outside diameter	\varnothing 210 mm
Width	\varnothing 210 mm
Depth	98 mm
Admiss. ambient temp.	0-40 °C
Weight	2.965 kg
Packing unit	1
Type of speaker	8"