





STA-400D

Order No.: 0255190

Price upon request

PRODUCTINFOS

The new generation of class D PA amplifiers from IMG STAGELINE impresses with a high power capability and high energy efficiency.

Other features include a silent operation and a low weight which make this series suitable for both fixed installations and mobile applications.

Stereo class D PA amplifier

- Class D concept with power amplifier modules from HYPEX
- 482 mm (19") rack installation, 1 RS, with supplied mounting brackets
- · Silent operation due to temperature-controlled fans
- Lightweight design due to compact switch-mode power supply
- Energy-efficient concept due to a high efficiency
- Powerful bass reproduction due to large buffer capacitors (high power reserves)
- 2 level controls
- Protected against short circuit and overtemperature
- LEDs for indicating power, overload (clip) and protect
- Super slimline design
- NEUTRIK SPEAKON connections

EVENT Rookie 01/2015

on the STA-400D and STA-800D

"Small and powerful surely applies to them. The two test units didn't really show any weakness. It should be noted that the minimum noise created by the two amplifiers is almost record-breaking ..."



TECHNICAL SPECIFICATIONS

STA-400D

Peak output power 700 W Power rating 540 W Power rating at 4 Ω 2 x 270 W Power rating at 8 Ω 2 x 180 W

Channels 2

Inputs 1 V/10 k Ω (XLR, bal.),

1 V/4.7 kΩ (RCA)

Frequency range 20-20,000 Hz

Integrated limiter no

S/N ratio > 110 dBA THD < 0.02% Mains voltage ~ 230 V Mains frequency 50 Hz Power consumption, operation 600 VA Admiss. ambient temp. 0-40 °C Width 482 mm Height 52 mm 277 mm Depth

Rack spaces, RS 1

Weight 3.5 kg

1 x 3-pole XLR L/R

 $1 \times RCA L/R$

Connections 1 x NEUTRIK SPEAKON L/R

2 x pair of screw terminals