



STA-700

Order No.: 0244120

Price upon request

PRODUCTINFOS

Stereo PA amplifier,

for general applications.

- Fan cooling
- 2 level controls
- Ground lift switch
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit, overheating and DC voltage overlay at the outputs
- 1 LED per channel for indicating overload (clip)

TECHNICAL SPECIFICATIONS

STA-700

Peak output power	800 W
Power rating	400 W
Power rating at 4 Ω	2 x 275 W
Power rating at 8 Ω	2 x 200 W
Channels	2
Inputs	0.85 V/55 k Ω

STA-700

Frequency range	10-20,000 Hz
Integrated limiter	yes
S/N ratio	85 dB
Crosstalk attenuation	> 43 dB
THD	< 0.05%
Mains voltage	230 V
Mains frequency	50 Hz
Power consumption, operation	1,100 VA
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	96 mm
Depth	296 mm
Rack spaces, RS	2
Weight	9.4 kg
Connections	1 x 6.3 mm jack L/R
	1 x RCA L/R
	2 x SPEAKER
	1 x 6.3 mm jack L/R
	2 x pair of screw terminals