



TFT-1904LED



Order No.: 0183100

Price upon request

PRODUCTINFOS

LCD colour monitor in a metal housing for surveillance systems,

with LED backlight for a very detailed image of high colour brilliance, with HDMI[™] connection.

- Visible diagonal screen size: 48 cm (19")
- Response time: 3.7 ms
- Viewing angle: 170° horizontal, 160° vertical
- Contrast ratio: 1,000:1
- Brightness: 250 cd/m², 16.7 million colours
- 2 video inputs, switchable, feed-through output
- 2 RCA audio inputs, feed-through output
- Additional connections: HDMI[™], DVI, VGA and S-video
- Built-in speaker
- Operation via on-screen menu (OSD)
- Display options: full image, picture-in-picture (PIP), picture-outside-picture (POP)
- Perforated rear panel according to VESA 100 standard
- Supplied with base, VGA cable, RCA audio cable and matching power supply

TECHNICAL SPECIFICATIONS

TFT-1904LED	
Colour system	PAL/NTSC
Screen diagonal	48 cm (19")
Resolution	1280 x 1024 pixels
Video input	1 Vpp/75 Ω
Video output	1 Vpp/75 Ω
Power supply	via encl. power supply
Admiss. ambient temp.	0-40 °C
Dimensions	425 x 352 x 53 mm (w/o base)
Weight	3.7 kg
	2 x BNC in (video 1+2) 2 x BNC out (video 1+2), feed-through output 1 x D-sub (VGA)
	1 x DVI
Connections	1 x HDMI™
	1 x S-video
	1 x 3.5 mm stereo jack, audio in
	1 x 3.5 mm stereo jack, audio in 2 x RCA, audio in
	•
	2 x RCA, audio in