



TXA-15USB

Order No.: 0173150

Price upon request

PRODUCTINFOS

Portable amplifier system,

with integrated Bluetooth receiver and USB/SD card player.

- Operation via mains connection or built-in lead gel battery 12 V/7.2 Ah (operating time: up to 6 hours), integrated automatic battery charging
- For mobile applications, e.g. sales events, lectures
- Bluetooth receiver for wireless connection of portable audio players
- Adjustable USB/SD card player with connection for external storage media
- 2-way speaker system
- 1 adjustable balanced microphone input via XLR, 1 adjustable microphone input via 6.3 mm mono jack, 1 adjustable CD/Tape input via RCA
- Adjustable master output with 3-way equalizer
- Link connection (6.3 mm jack) for combining several TXA-15USB systems
- Cabinet in flight case design, with drop handles
- Due to integrated extractable telescopic handle and 2 castors, amplifier system can easily be pulled like a trolley
- Stand sleeve

TECHNICAL SPECIFICATIONS

TXA-15USB

Rated power (P_{RMS})	15 W
Peak output power	20 W
Frequency range	70-20,000 Hz
Inputs	6 mV (mic), 600 mV (line)
Link	380 mV
Equalizer, bass	± 15 dB/100 Hz
Equalizer, midrange	± 15 dB/2.5 kHz
Equalizer, treble	± 15 dB/10 kHz
Power supply	~ 230 V/50 Hz/60 VA, rech. battery: 12 V/7.2 Ah
Admiss. ambient temp.	0-40 °C
Dimensions	410 x 470 x 310 mm
Weight	16.4 kg
Connections	1 x XLR (mic), 1 x 6.3 mm jack (mic), 1 x RCA L/R (line), 1 x 6.3 mm jack (link)