



## TXA-700USB

Order No.: 0174750

**Price upon request**

### PRODUCTINFOS

#### **Portable amplifier system,**

with wireless microphone, integrated Bluetooth receiver and USB/SD card player.

- High-performance class D version 80 W, with optimum efficiency
- Operation via mains connection or built-in lead gel battery 2 x 12 V/5 Ah (operating time: up to 6 hours), integrated automatic battery charging
- For mobile applications, e.g. sales events, lectures
- Wireless microphone with adjustable wireless UHF receiver
- Bluetooth receiver for wireless connection of portable audio players
- Adjustable USB/SD card player with connection for external storage media
- Remote control
- 2-way speaker system
- 2 adjustable inputs via comb. jacks (XLR/6.3 mm jack), switchable mic/line
- 1 aux input (3.5 mm jack, RCA)
- Adjustable reverb
- Common master control with 2-way tone control
- 1 line output (6.3 mm jack)
- Due to integrated extractable telescopic handle and 2 castors, amplifier system can easily be pulled like a trolley

- Stand sleeve

**Licence-free in the EU.**

## TECHNICAL SPECIFICATIONS

### TXA-700USB

|                           |   |
|---------------------------|---|
| Rated power ( $P_{RMS}$ ) | 80 W  |
| Peak output power         | 120 W   |
| Frequency range           | 55-20,000 Hz  |
| Carrier frequency         | 863-865 MHz   |
| Inputs                    | 10 mV (mic),<br>950 mV (line),<br>1.4 V (aux)   |
| Equalizer, bass           | $\pm 12$ dB/55 Hz   |
| Equalizer, treble         | $\pm 12$ dB/15 kHz  |
| Power supply              | $\sim 230$ V/50 Hz/40 VA,<br>rech. battery: 2 x 12 V/5 Ah   |
| Admiss. ambient temp.     | 0-40 °C   |
| Dimensions                | 360 x 560 x 325 mm  |
| Weight                    | 17 kg   |
| Connections               | 2 x XLR/6.3 mm jack (mic/line),<br>1 x RCA L/R (aux),<br>1 x 3.5 mm jack (aux),<br>1 x 6.3 mm jack (line out) |