



ECM-950

Order No.: 23.3280

EUR 99,90

RRP *

PRODUCTINFOS

Electret directional microphone,

with switchable pick-up pattern, for crucial outdoor recordings at video productions and film productions.

- Supplied with microphone holder, microphone windshield, 50 cm helix cable, 7.5 m cable and plastic case

TECHNICAL SPECIFICATIONS

ECM-950

Type	directional microphone
Transmission method	cable
Polar pattern	cardioid/supercardioid
System	electret

ECM-950

Carrier frequency range	-
Transmitting power	-
Power supply	-
Operating time	-
Audio frequency range	50-16000Hz
Nominal impedance	normal 1 k Ω /tele 2.3 k Ω
Sensitivity	3/22 mV/Pa
S/N ratio	60dB
Maximum sound pressure	115dB
Power supply	1.5 V batt. AA size
Gooseneck length	-
Material (housing/cabinet)	metal
Admiss. ambient temp.	0-40°C
Dimensions	Ø 22 mm x 285 mm
Weight	350g
Cable	0.5 m/7.5 m
Connection	3.5 mm plug

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.