



EDL-70/WS

Order No.: 16.3310

EUR 29,90

RRP *

PRODUCTINFOS

PA ceiling speaker,

with special 2-step mounting.

- 100 V line technique
- Snap-in mounting
- For a ceiling thickness from 2 to 45 mm
- Full range speaker with a clear voice reproduction
- Wide frequency range
- Robust metal version (basket and protective grille)

For mounting this PA ceiling speaker, the mounting frame is attached to the ceiling cutout at first via the snap-in system. Then, the speaker is inserted into the frame with a bayonet-type locking. A safety rope provides additional safety.

TECHNICAL SPECIFICATIONS

EDL-70/WS

Impedance (Z)	-
Operating voltage	100 V
Frequency range	90-20000 Hz
Resonant frequency (fs)	-
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	-
Power rating	6/3/1.5 W
Peak music power output	-
Sensitivity	97 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle, horizontal	-
Radiation angle, vertical	-
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	-
Voice coil former	-
Linear excursion (X_{MAX})	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	-
Mounting cutout	Ø195 mm
Mounting depth	100 mm
Mounting hole diameter	-
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	Ø 220 mm x 104 mm
Outside diameter	Ø220 mm
Width	Ø220 mm

EDL-70/WS

Height	-
Depth	104 mm
Protective class	-
Admiss. ambient temp.	-
Weight	1,13 kg
Sales unit	-
Type of speaker	165

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.