



MMX-602/SW

Order No.: 20.2230

EUR 289,00

RRP *

PRODUCTINFOS

Microphone line mixer,

6 channels.

- 6 stereo line inputs, 6 balanced mono microphone inputs, switchable
- Adjustable automatic talkover (-12 dB), switchable for channel 1 or channels 1+2
- Balance control for each stereo input channel
- 3-way equalizer
- 12 V phantom power can be switched on additionally
- LED VU meter, peak LED
- Master output and record output
- Output can be switched stereo/mono
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RS

TECHNICAL SPECIFICATIONS

MMX-602/SW

No. of channels	6
No. of inputs	12
Mic input	1 mV/6.6 k Ω , 6 x 3-pole XLR, bal.
Line input	100 mV/10 k Ω , 6 x RCA L/R

MMX-602/SW

CD input	-
Phono input	-
Tape (play)	-
Aux input	-
Insert input	-
effect return	-
Master output	1 V/600 Ω , 1 x RCA L/R 1 x 3-pole XLR L/R, bal.
Record output	310 mV/600 Ω , 1 x RCA L/R
Monitor output	-
Booth output	-
Aux output	-
Insert output	-
effect send	-
Control room	-
Tape (rec)	-
Headphones	> 8 Ω , 1 x 6.3 mm jack
Gooseneck lamp	-
WiFi	-
USB	-
Frequency range	20-20000 Hz
THD	0,1%
S/N ratio	62 dB, unweighted
Crosstalk	-
Equalizer bass	± 12 dB/50 Hz
Equalizer midrange	± 12 dB/1 kHz
Equalizer treble	± 12 dB/10 kHz
equalizer	-
Talkover	-12 dB, manual
Phantom power	-
Crossfader	-
Media player	-
Amplifier	-
Power supply	~ 230 V/50 Hz/12 VA
Mains voltage	~230 V
Mains frequency	50 Hz
Power consumption, operation	12 VA
Alternative operating voltage	-

MMX-602/SW

Alternative power supply	-
Admiss. ambient temp.	0-40 °C
Width	482 mm
Height	47 mm
Depth	208 mm
Rack spaces, RS	1
Weight	2,8 kg

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.