



PA-12040

Order No.: 17.3390

EUR 1029,00

RRP *

PRODUCTINFOS

4-channel mono mixing amplifiers,

with professional features for general multi-room PA applications.

- 4 x 120 W (PA-12040)
- 4 x 40 W (PA-4040)
- 100 V and 4/8 Ω operation
- Perfect utilisation of the capacity and reliable protection of connected speakers due to an integrated limiter
- 3 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control, channel mute switch and zone routing switch
- Microphone inputs with +46 V phantom power, can be switched on additionally as desired
- Priority function for channel 1, switchable
- Independent paging input, can be routed to all zones
- 4 zone outputs, can be controlled individually
- Zone and monitor line outputs for additional amplifiers or recorders
- Connection for monitor speakers
- Level control via VU meters for zone and monitor

- Adjustable headphone output
- Fan cooling
- 230 V mains operation

TECHNICAL SPECIFICATIONS

PA-12040

Channels	5
Zones	4
Power rating	4 x 120 W
Power rating at 2 Ω	-
Power rating at 4 Ω	-
Power rating at 8 Ω	-
Power rating at 100 V	-
Power rating with 4 Ω bridged operation	-
Power rating with 8 Ω bridged operation	-
Peak music power output (P_{MAX})	4 x 170 W
Output impedance	-
Inputs	5 mV/4 k Ω , 100 mV/10 k Ω (mic/line) 100 mV/30 k Ω (line) 40 mV/5 k Ω (tel. paging)
Attenuation factor	-
Frequency range	50-17,000 Hz
Crossover network	-
Crossover frequency	-
Integrated limiter	yes
Equalizer bass	± 10 dB/100 Hz
Equalizer midrange	-
Equalizer treble	± 10 dB/10 kHz
S/N ratio	> 65 dB, mic > 75 dB, line
Crosstalk attenuation	-
THD	<1%
Power supply	~ 230 V/50 Hz/1,200 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1200 VA
Power consumption, standby	-
Standby current	-

PA-12040

Alternative operating voltage	-
Alternative power supply	-
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 133 x 410 mm, 3 RS
Width	482 mm
Height	133 mm
Depth	410 mm
Rack spaces, RS	-
Weight	20,5 kg
Connections	3 x combo jack/XLR, bal. (mic/line inputs) 2 x RCA L/R (line inputs) 3.5 mm jack (headphones) screw terminal (paging, priority, zone outputs, speakers, line outputs)

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.