



STA-1508

Order No.: 24.4300

EUR 649,00

RRP *

PRODUCTINFOS

Multi-channel PA amplifiers,

with integrated limiter.

STA-1508 = 8 channels

STA-1506 = 6 channels

STA-1504 = 4 channels

- Balanced inputs
- High-pass filter, low-pass filter, can be switched on additionally for each channel
- Tamper-resistant level adjustment on the rear panel
- 8 Ω bridged operation possible
- LED VU meter and LED per channel for indicating overload (clip)
- Soft start
- Ground lift switch
- Speaker switch-on delay
- Fan cooling
- Protected against short circuit, overheating and DC voltage overlay at the outputs

TECHNICAL SPECIFICATIONS

STA-1508

Channels	8
Zones	-
Power rating	1280 W
Power rating at 2 Ω	-
Power rating at 4 Ω	8 x 160 W
Power rating at 8 Ω	8 x 100 W
Power rating at 100 V	-
Power rating with 4 Ω bridged operation	-
Power rating with 8 Ω bridged operation	4 x 320 W
Peak music power output (P_{MAX})	1800 W
Output impedance	-
Inputs	0.7 V/20 k Ω
Attenuation factor	-
Frequency range	12-60000 Hz
Crossover network	yes
Crossover frequency	240 Hz
Integrated limiter	yes
Equalizer bass	-
Equalizer midrange	-
Equalizer treble	-
S/N ratio	>80 dB
Crosstalk attenuation	>60 dB
THD	<0,1%
Power supply	~ 230 V/50 Hz/2,400 VA
Mains voltage	~230 V
Mains frequency	50 Hz
Power consumption, operation	2400 VA
Power consumption, standby	-
Standby current	-
Alternative operating voltage	-
Alternative power supply	-
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 132 x 310 mm, 3 RS
Width	482 mm
Height	132 mm

STA-1508

Depth	310 mm
Rack spaces, RS	3
Weight	16,7 kg
Connections	8 x 3-pole XLR, bal. 8 x screw terminal

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.