



STA-225

Order No.: 25.3340

EUR 369,00

RRP *

PRODUCTINFOS

Stereo PA amplifier, 700 W,

with integrated limiter.

- LCD for indicating temperature, operating mode, power
- 2 operating modes can be selected (stereo or bridged)
- Limiter function can be switched on additionally
- Temperature-controlled fan
- 2 level controls
- Ground lift function
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit and overheating
- Each channel with LEDs for indicating limiter, level and signal

tastenwelt 02/2012

"The plastic housings are of neat workmanship ... the MMX-842USB is a good choice ... the STA-225 features all standard protective circuits, even a clip limiter can be switched on additionally. A display shows useful information on the operation. The system tested provided a really appealing sound: a nice deep bass reproduction and a clear midrange of the 12" speakers and a full and clear reproduction of the high

frequencies, too. With the support of a subwoofer, the volume which can be achieved is already sufficient to show a great performance at smaller to medium-sized events. Neither the active bass speaker nor the passive top parts provide an unpleasant or even overstrained sound."

(PA setup of PAB-112MK2, PSUB-115AK, STA-225, MMX-842USB)

TECHNICAL SPECIFICATIONS

STA-225

Channels	2
Zones	-
Power rating	700 W
Power rating at 2 Ω	-
Power rating at 4 Ω	2 x 350 W
Power rating at 8 Ω	2 x 250 W
Power rating at 100 V	-
Power rating with 4 Ω bridged operation	-
Power rating with 8 Ω bridged operation	1 x 700 W
Peak music power output (P_{MAX})	1000 W
Output impedance	-
Inputs	1.3 V/10 k Ω
Attenuation factor	-
Frequency range	10-50,000 Hz
Crossover network	-
Crossover frequency	-
Integrated limiter	-
Equalizer bass	-
Equalizer midrange	-
Equalizer treble	-
S/N ratio	>80 dB
Crosstalk attenuation	>50 dB
THD	<0,1%
Power supply	~ 230 V/50 Hz/1,500 VA
Mains voltage	~230 V
Mains frequency	50 Hz
Power consumption, operation	1500 VA
Power consumption, standby	-
Standby current	-
Alternative operating voltage	-

STA-225

Alternative power supply	-
Admiss. ambient temp.	-
Dimensions	482 x 100 x 330 mm, 2 RS
Width	482 mm
Height	100 mm
Depth	330 mm
Rack spaces, RS	2
Weight	10,3 kg
Connections	1 x 3-pole XLR L/R, bal. 1 x 6.3 mm jack L/R, bal. 3 x SPEAKER 2 x pair of screw terminals

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.