



STA-235

Order No.: 25.3210

EUR 439,00

RRP *

PRODUCTINFOS

Stereo PA amplifier,

with integrated limiter.

- LCD for indicating temperature, operating mode, power
- 2 operating modes can be selected (stereo or bridged)
- Limiter function can be switched on additionally
- Temperature-controlled fans
- 2 level controls
- Ground lift function
- Speaker switch-on delay
- Protective circuit with LED indication for protection against short circuit and overheating
- Each channel with LEDs for indicating overload, level and signal

TECHNICAL SPECIFICATIONS

STA-235

Channels	2
Zones	-

STA-235

Power rating	1000 W
Power rating at 2 Ω	-
Power rating at 4 Ω	2 x 500 W
Power rating at 8 Ω	2 x 400 W
Power rating at 100 V	-
Power rating with 4 Ω bridged operation	-
Power rating with 8 Ω bridged operation	1 x 1000 W
Peak music power output (P_{MAX})	1400 W
Output impedance	-
Inputs	1.2 V/10 k Ω
Attenuation factor	-
Frequency range	10-50,000 Hz
Crossover network	-
Crossover frequency	-
Integrated limiter	yes
Equalizer bass	-
Equalizer midrange	-
Equalizer treble	-
S/N ratio	>80 dB
Crosstalk attenuation	>50 dB
THD	<0,1%
Power supply	~ 230 V/50 Hz/2,000 VA
Mains voltage	~230 V
Mains frequency	50 Hz
Power consumption, operation	2000 W
Power consumption, standby	-
Standby current	-
Alternative operating voltage	-
Alternative power supply	-
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 100 x 330 mm, 2 RS
Width	482 mm
Height	100 mm
Depth	330 mm
Rack spaces, RS	2
Weight	11,5 kg

STA-235

Connections

1 x 3-pole XLR L/R, bal. 1 x 6.3 mm jack
L/R, bal. 3 x SPEAKER 2 x pair of screw
terminals

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.