



TXS-606DT

Order No.: 25.7310

EUR 174,90

RRP *

PRODUCTINFOS

Wireless desktop microphone with integrated multifrequency transmitter,

with UHF PLL technology.

- Electret microphone cartridge, cardioid polar pattern
- 350 mm gooseneck, removable
- 1,000 selectable UHF frequencies (672.000-696.975 MHz), can be synchronised with receivers TXS-606, TXS-626, TXS-646 or TXS-686 via ACT function
- Adjustable sensitivity
- Switchable transmitting power (high: 25 mW/low: 2.5 mW)
- LCD for indicating group/channel, audio level and battery status
- Power supply via 2 x 1.5 V battery AA size (not supplied)

Licence required for this system in the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

TECHNICAL SPECIFICATIONS

TXS-606DT

Type	desktop microphone
Transmission method	wireless
Polar pattern	cardioid
System	electret
Carrier frequency range	672,000-696,975MHz
Transmitting power	25 mW/2.5 mW
Power supply	2 x 1.5 V batt. AA size
Operating time	>8h
Audio frequency range	30-18000Hz
Nominal impedance	-
Sensitivity	-
S/N ratio	-
Maximum sound pressure	-
Power supply	-
Gooseneck length	-
Material (housing/cabinet)	-
Admiss. ambient temp.	0-40°C
Dimensions	120 x 65 x 178 mm(w/o gooseneck)
Weight	600g
Cable	-
Connection	-

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.