



TXS-812SET

Order No.: 25.2600

EUR 265,00

RRP *

PRODUCTINFOS

Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in PSU
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

TXS-812SET

General information -

TXS-812SET

Type	wireless microphone system
Carrier frequency range	863.80 MHz , 864.20 MHz
Audio frequency range	40-15000Hz
Channels	2
THD	<0,5%
Dynamic range	>90dB
RF S/N ratio	>80dB
Operating time	-
Admiss. ambient temp.	0-40°C
Power supply	-
Dimensions	-
Total weight	-
Connections	-
Specifications transmitter	-
Transmitting power	<10mW
Operating range	approx. 30 m
Power supply transmitter	2 x 1.5 V batt. AA size (not supplied)
Width transmitter	52mm
Height transmitter	52mm
Depth transmitter	260mm
Weight transmitter	240g
Connections transmitter	-
Specifications receiver	-
Audio signal receiver	0-200 mV/10 kΩ (jack)0-400 mV/10 kΩ (XLR, bal.)
Power supply receiver	via suppl. plug-in PSU
Width receiver	210mm
Height receiver	46mm
Depth receiver	190mm
Weight receiver	560g
Connections receiver	2 x XLR, bal.1 x 6.3 mm jack, unbal.

* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.